

High Performance Insulation for Under Concrete Floors

3.0
R-VALUE
@100mm

200kPa
STRENGTH
@ 10%
DEFORMATION



NEW GENERATION
Consciously designed
& engineered

- A cost effective alternative to XPS
- Specifically designed for insulating under concrete floors
- Uncompromised strength ● Exceptional insulation values



SLABX200 High Performance Expanded Polystyrene for under Concrete Floor (SLAB) Insulation

SLABX200 is EXPOL's new generation high performance Expanded Polystyrene Board specifically designed to deliver high compressive strength and improve insulation under concrete slabs.

It delivers an uncompromised compressive strength of 200kPa @ 10% deformation and exceptional Insulation Values.

Specifically engineered for residential and commercial projects, its high performance gives engineers and specifiers peace of mind while increasing the thermal performance of a building.

SLABX200's durable nature means it will not degrade over time, keeping its integrity for the life of the structure.

SLABX200 increases the thermal performance of a building


- A cost effective alternative to XPS
- Uncompromised compressive strength 200kPa @ 10% deformation
- Exceptional Insulation Values
- High water resistance
- Lightweight and easy to handle
- Various thicknesses from 50mm to 600mm
- SLABX200 waste is actively recycled into other EXPOL products



SLABX200 Technical Specifications

Property	Unit	EXPOL SLABX200	Test Reference
Material		Expanded Polystyrene	
Density	kg/m3		
Thickness* / R Value	m2K/W		ASTM C518-04
	50mm	R 1.50	
	75mm	R 2.20	
	100mm	R 3.00	
	150mm	R 4.50	
	200mm	R 6.00	
Compressive Resistance	KPA at 1%	92	AS 2498.3
Compressive Resistance	KPA at 2%	145	
Compressive Resistance	KPA at 5%	184	
Compressive Resistance	KPA at 10%	200	

* Other thicknesses are available on request



Sheet Sizes

	Length (mm)	Width (mm)
EXPOL SLABX200	2400	1200

RECYCLING PROPERTIES

EXPOL SLABX200 (EPS – Expanded Polystyrene) can be easily recycled.

MANUFACTURING STANDARD

All products and grades of Expanded Polystyrene supplied by EXPOL for retaining walls, concrete floors, pod floors, skillion roofs, cladding insulation, wall insulation, lightweight fill comply with manufacturing standard AS 1366 Part 3 1992.



Learn about our recycling initiatives



Sustainability
E: sustainability@expolearth.co.nz

Website
www.expolearth.co.nz



Contact EXPOL
P: +64 9 634 3449
F: +64 9 634 0756

Sales
T: 0800 86 33 73
E: sales@expol.co.nz

Quotes/Technical
T: 0800 86 33 73
E: tech@expol.co.nz

EXPOL Product Training
T: 0800 86 33 73
www.expolexpert.co.nz

Website
www.expol.co.nz