

5

Environmental Product Declaration Plywood



Environmental Product Declaration (EPD)
in accordance with ISO 14025 and EN 15804

EPD Registration No. S-P-00564 | Version 1
Issued 14 October 2015 | Valid until 14 October 2020

Geographical Scope: Australia



Environmental Product Declarations

WoodSolutions has developed a suite of EPDs for industry-average, Australian-produced timber products.

These EPDs help to showcase the environmental credentials of Australian wood products. They also provide life cycle data for calculating the impacts of wood products at a building level.

EPDs include:

- #01 Softwood Timber
- #02 Hardwood Timber
- #03 Particleboard
- #04 Medium Density Fibreboard (MDF)
- #05 Plywood

WoodSolutions is an industry initiative designed to provide independent, non-proprietary information about timber and wood products to professionals and companies involved in building design and construction.

WoodSolutions is resourced by Forest and Wood Products Australia (FWPA). It is a collaborative effort between FWPA members and levy payers, supported by industry peak bodies and technical associations.

This work is supported by funding provided to FWPA by the Commonwealth Government.

978-1-925213-18-8

Researchers:

Timber Development Association (NSW) Ltd
Suite 604-486 Pacific Highway
St Leonards NSW 2065

thinkstep Pty Ltd
25 Jubilee Street
South Perth WA 6151

Produced: October 2015

© 2015 Forest and Wood Products Australia Limited. All rights reserved.

These materials are published under the brand WoodSolutions by FWPA.

IMPORTANT NOTICE

Whilst all care has been taken to ensure the accuracy of the information contained in this publication, Forest and Wood Products Australia Limited and WoodSolutions Australia and all persons associated with them (FWPA) as well as any other contributors make no representations or give any warranty regarding the use, suitability, validity, accuracy, completeness, currency or reliability of the information, including any opinion or advice, contained in this publication. To the maximum extent permitted by law, FWPA disclaims all warranties of any kind, whether express or implied, including but not limited to any warranty that the information is up-to-date, complete, true, legally compliant, accurate, non-misleading or suitable.

To the maximum extent permitted by law, FWPA excludes all liability in contract, tort (including negligence), or otherwise for any injury, loss or damage whatsoever (whether direct, indirect, special or consequential) arising out of or in connection with use or reliance on this publication (and any information, opinions or advice therein) and whether caused by any errors, defects, omissions or misrepresentations in this publication. Individual requirements may vary from those discussed in this publication and you are advised to check with State authorities to ensure building compliance as well as make your own professional assessment of the relevant applicable laws and Standards.

The work is copyright and protected under the terms of the Copyright Act 1968 (Cwth). All material may be reproduced in whole or in part, provided that it is not sold or used for commercial benefit and its source (Forest & Wood Products Australia Limited) is acknowledged and the above disclaimer is included. Reproduction or copying for other purposes, which is strictly reserved only for the owner or licensee of copyright under the Copyright Act, is prohibited without the prior written consent of FWPA.

WoodSolutions Australia is a registered business division of Forest and Wood Products Australia Limited.

EPD Details

An Environmental Product Declaration, or EPD, is a standardised and verified way of quantifying the environmental impacts of a product based on a consistent set of rules known as a PCR (Product Category Rules).

Environmental product declarations within the same product category from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804.

Declaration owner:

Forest and Wood Products Australia Ltd

Web: www.fwpa.com.au

Email: info@fwpa.com.au

Post: Level 4, 10-16 Queen Street, Melbourne VIC 3000, Australia



EPD produced by:

thinkstep Pty Ltd

Web: www.thinkstep.com

Email: anz@thinkstep.com

Post: 25 Jubilee Street, South Perth WA 6151, Australia



Stephen Mitchell, Timber Development Association (NSW) Ltd

Web: www.tdansw.asn.au

Email: info@tdansw.asn.au

Post: Suite 604-486 Pacific Highway, St Leonards NSW 2065, Australia



EPD programme operator:

The Australasian EPD® Programme Ltd

Web: www.epd-australasia.com

Email: info@epd-australasia.com

Post: c/o Enviro-Mark Solutions Ltd
PO Box 69040, Lincoln 7640, New Zealand



CEN standard EN 15804 served as the core PCR

PCR:

PCR 2012:01 Construction products and Construction services, Version 2.0, 2015-03-03

PCR review was conducted by:

The Technical Committee of the International EPD® System.

Chair: Massimo Marino. Contact via info@environdec.com.

Independent verification of the declaration and data, according to ISO 14025:

EPD process certification (Internal)

EPD verification (External)

Third party verifier

Benjamin Canaguier, Catalyst Ltd

Web: www.catalystnz.co.nz

Email: activate@catalystnz.co.nz

Post: PO Box 37228, Christchurch 8245, New Zealand



Accredited or approved by: The Australasian EPD® Programme

Introduction

This Environmental Product Declaration presents the average performance of plywood manufactured in Australia from Australian grown wood by members of Forest and Wood Products Australia (FWPA). It recognises the importance of transparency by providing information on the raw materials, production and environmental impacts of Australian plywood.

This EPD has been prepared in accordance with ISO 14025:2006, EN 15804:2013, PCR 2012:01 and AEPDP (2015). It covers plywood panels produced in accordance with the following standards:

- AS/NZS 2269: 2012 Plywood – Structural – Specifications
- AS/NZS 2270: 2006 Plywood and Blockboard for Interior Use
- AS/NZS 2271: 2004 Plywood and Blockboard for Exterior Use
- AS/NZS 2272: 2006 Plywood – Marine
- AS 6669: 2007 Plywood Formwork

The environmental data presented in this document were largely from a survey of industry members conducted by CSIRO on behalf of FWPA (CSIRO 2009). This study covered 90% of total plywood production in Australia. Production of the EPD and validation of the data have been facilitated by FWPA with the participation of its current plywood producer members (listed at the end of this section) and the Engineered Wood Products Association of Australasia (EWPA).

Description of the Australian Plywood Industry

The Australian plywood manufacturing industry is an important contributor to the Australian economy – particularly in the regional areas where many plywood mills are based. The overall contribution of the wood and wood products industries to the Australian GDP in 2010-11 was 0.59% (or \$8.3 billion added value) (ABARES 2013). In 2013-2014, Australian plywood manufacturers produced 145,000 cubic metres of plywood products (ABARES 2014) in five different facilities.

Description of Plywood Products

Plywood is a panel product made of thin veneers of wood peeled from softwood and hardwood logs and bonded by resin. Plywood products are either engineered wood panels (such as structural plywood and formwork plywood) or non-structural panels (such as interior and exterior plywood). The difference between the engineered products and the non-structural products is that engineered products have standardised structural properties, such as strength, stiffness and dimensional stability.

Plywood is used in many application areas, such as structural bracing, concrete formwork, cladding, flooring, webbed beams, boats, aircraft, door skins, furniture, wall panels and architectural joinery in exterior and interior environments.

Use of EPDs within Green Star

This document complies with the requirements for an industry-wide EPD under the Green Building Council of Australia's Green Star rating system given that:

1. It conforms with ISO 14025 and EN 15804.
2. It has been verified by an independent third party.
3. It has at least a cradle-to-gate scope.
4. The participants in the EPD are listed (see below).

It may be used by project teams to obtain points under the Materials category of the current *Design & As Built* and *Interiors* rating tools, as well as under the Innovation Challenge category of the legacy Green Star rating tools.

It can also help project teams conduct a Green Star compliant whole-of-building, whole-of-life Life Cycle Assessment to obtain additional points under the Materials category of the current *Design & As Built* and *Interiors* rating tools as well as under the Innovation Challenge category of the legacy Green Star rating tools.

This EPD applies to the following companies:

- Ausply Pty Ltd (Wagga Wagga, New South Wales)
- Austral Plywoods (Brisbane, Queensland)
- Big River Timbers (Grafton, New South Wales)
- Carter Holt Harvey (Myrtleford, Victoria)
- Ta Ann Tasmania (Smithton, Tasmania).

Products

This Sector EPD describes the following average products (declared units) manufactured in Australia by the FWPA members listed in the Introduction:

- 1 m² of interior plywood, C-bond, 9 mm (joinery)
- 1 m² of exterior plywood, A-bond, 7 mm (bracing)
- 1 m² of exterior plywood, A-bond, 9 mm (structural)
- 1 m² of formply, A-bond, 17 mm (formwork)
- 1 m² of plywood flooring, tongue and groove, A-bond, 15 mm (residential)
- 1 m² of plywood flooring, tongue and groove, A-bond, 25 mm (commercial)

Wood used in these products is from Australian grown native and exotic (non-native) softwood species grown in plantations as well as hardwood species grown in native forests. The dominant softwood species used to produce plywood in Australia is *Pinus radiata* (radiata pine). Other softwood species used are *Araucaria cunninghami* (hoop pine), *Pinus pinaster* (maritime pine) and the Southern Pines: *Pinus elliottii* (slash pine), *Pinus caribaea* (Caribbean pine) and hybrids thereof. Hardwood species are a variety of species harvested in NSW, Queensland, Victoria and Tasmania.

The properties and material composition of these products are defined in Table 1 and Table 2 below.

Table 1: Properties of plywood products included in this EPD.

Properties	Int 9 mm	Ext 7 mm	Ext 9 mm	Form 17 mm	Floor 15 mm	Floor 25 mm
Area density (kg per m ²)	5.42	4.22	5.42	10.2	9.03	15.1
Density (kg per m ³)	602	602	602	602	602	602
Moisture content (dry basis)	12%	12%	12%	12%	12%	12%
Gross calorific value (MJ/kg)	19.6	20.7	20.7	20.7	20.9	20.8
Net calorific value (MJ/kg)	16.2	17.3	17.3	17.3	17.6	17.5
CO ₂ sequestered (kg CO ₂ e)	7.96	6.19	7.96	15.0	13.2	22.0

Table 2: Composition of plywood products included in this EPD.

Materials	Int 9 mm	Ext 7 mm	Ext 9 mm	Form 17 mm	Floor 15 mm	Floor 25 mm
Softwood veneer (dry)	70.7%	70.7%	70.7%	70.7%	70.1%	70.3%
Hardwood veneer (dry)	8.6%	8.6%	8.6%	8.6%	8.5%	8.5%
Paper (dry)	0.9%	0.9%	0.9%	0.9%	0.9%	0.9%
Phenol formaldehyde	0.3%	7.4%	7.4%	7.4%	7.3%	7.3%
Urea formaldehyde	7.1%	0.0%	0.0%	0.0%	0.0%	0.0%
Preservative (dry) *	0.1%	0.1%	0.1%	0.1%	0.1%	0.1%
Other, in glue mix (dry)	1.6%	1.6%	1.6%	1.6%	1.6%	1.6%
Acrylic putty	0.1%	0.1%	0.1%	0.1%	0.1%	0.1%
Polypropylene (tongue)	0.0%	0.0%	0.0%	0.0%	0.7%	0.4%
Water	10.7%	10.7%	10.7%	10.7%	10.7%	10.7%
Total	100.00%	100.00%	100.00%	100.00%	100.00%	100.00%

* Preservative treatment is particularly common for plywood used in wet areas, such as flooring and external plywood. Preservatives include Chromated Copper Arsenate (CCA), Light Organic Solvent Preservative (LOSP), Alkaline Copper Quaternary (ACQ) and synthetic pyrethroids. The value in Table 2 is an industry average of total preservative use across all plywood product types. However, please note that some plywood is untreated. For information on the specific preservative used in a specific product, please contact your supplier.

The data in Table 1 and Table 2 exclude packaging and any markings applied to the surface of the board. On average, markings on the product per cubic metre of plywood require 0.375 kg paint and 0.013 kg ink. Average packaging per cubic metre of plywood requires 0.150 kg steel strapping and 0.017 kg plastic.

The declared units above represent an entire product category rather than a specific product from a specific manufacturer. As such, a specific product purchased on the market may have a lesser or greater environmental impact than the average presented in this EPD. Some products may also undergo further processing (e.g. sawing) before being used in a building.

Representativeness

Approximately 90% of plywood production in Australia was covered in the original survey (CSIRO 2009).

Data from this study were predominantly from the 2005-06 financial year. Since this time, the number of plywood mills has decreased from eight to four, with a new mill by Ta Ann in Tasmania expected to commence production in late 2015. All remaining mills employ the same production technology as they did at the time of the original study. As such, TDA and FWPA consider the 2005-06 data to be a good representation of today's conditions. FWPA will monitor for any major changes within the industry during the period of validity of this EPD (2015 to 2020) and update or withdraw this EPD should any such changes occur.

Industry Classifications

Product	Classification	Code	Category
All	UN CPC Ver.2	31410	Plywood consisting solely of sheets of wood, except of bamboo
All	ANZSIC 2006	1493	Veneer and Plywood Manufacturing

LCA Calculation Rules

System Boundary

This EPD is of the 'cradle-to-gate' type with options. The options include the end-of-life stage, which is modelled through the use of scenarios.

Product stage			Con- struction process stage		Use stage							End-of-life stage				Benefits and loads beyond the system boundary
Raw material supply	Transport of raw materials	Manufacturing	Transport to customer	Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction / demolition	Transport to waste processing	Waste processing	Disposal	Reuse- Recovery- Recycling- potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	X	X	X

Key: X = included in the EPD

ND = not declared (such a declaration shall not be regarded as an indicator result of zero)


Production

Australian plywood can be produced from softwood or hardwood, with softwood plywood being the most common. This EPD represents average conditions, which includes 92% softwood veneer and 8% hardwood veneer by volume.

The manufacturing process starts by debarking and softening logs. Logs are then cut into billets and rotary peeled to produce veneers approximately 1 mm in thickness. The veneers are clipped, dried and then graded by appearance. Defects are repaired using putty.

Finished veneers are resin-bonded with the grain direction of each layer perpendicular to that of the previous layer and then hot pressed into a panel. A-bond (phenol formaldehyde) resin is most common, with C-bond (urea formaldehyde) resin used for internal joinery. The final board is cut to size, sanded, finished (e.g. with added grooves and polypropylene tongue for flooring) and then labelled/branded using ink or paint.

Depending on the product type, stacks of plywood may be left loose, held together with steel straps or wrapped in plastic film. A weighted average of all options is considered within this EPD.



End-of-Life

When a wood product reaches the end of its useful life, it may either be reused, recycled, landfilled or combusted to produce energy. Landfill is currently the most common end-of-life route for wood products in Australia. Reuse is also common for plywood formwork. All other scenarios are in use in certain regions (Forsythe Consultants 2007; National Timber Product Stewardship Group) and have been included within this EPD.

Each scenario assumes that 100% of the wood is sent to that scenario. To create an end-of-life mix for a given region or end use, the reader should take a weighted sum of these scenarios. Where no data are available, the 'landfill (typical)' scenario should be used for 100% of the waste.

Landfill

This EPD includes two scenarios for landfill, each with a different value for the degradable organic carbon fraction (DOCf) of wood. The two values are based on bioreactor laboratory research. This experimental work involves the testing of a range of waste types in reactors operated to obtain maximum methane yields. As the laboratory work optimises the conditions for anaerobic decay, the results can be considered as true estimates of the DOCf value that would apply over very long time horizons (Australian Government 2014a, p. 17).

- **Landfill (typical):** DOCf = 1.4%. This is based on bioreactor laboratory research by Wang et al. (2011). This value can be considered as an upper limit for degradation of carbon in solid wood placed in a landfill.
- **Landfill (NGA):** DOCf = 23%. This is the value chosen for Australia's National Greenhouse Accounts (NGA). It was derived from early bioreactor laboratory research from the 1990s (e.g. Barlaz 1998) that investigated the degradability of wood tree branches ground to a fine powder under anaerobic conditions (Australian Government 2014a, p. 17). This value can be considered as an upper limit for degradation of carbon in finely ground timber placed in a landfill.

The impacts associated with the landfill are declared in module C4. All landfill gas that is combusted for energy recovery (module C4) is assumed to occur in a power plant with an electrical conversion efficiency of 36% (Australian Government 2014c, p. 189) and the resulting electricity receives a credit for offsetting average electricity from the Australian grid (module D) in line with EN 16485:2014 (Section 6.3.4.5).

Both landfill scenarios assume the following for carbon emissions:

- Of the gases formed from any degradation of wood in landfill, 50% is methane and 50% is carbon dioxide (Australian Government 2014b).
- All carbon dioxide is released directly to the atmosphere.
- 36% of the methane is captured, based on forecasted average methane capture in Australian landfills by 2020 (Hyder Consulting 2007). Of this, one quarter (9% of the total) is flared and three quarters (27% of the total) are used for energy recovery (Carre 2011).
- Of the 64% of methane that is not captured, 10% (6.4% of the total) is oxidised (Australian Government 2014b) and 90% (57.6%) is released to the atmosphere.
- In summary, for every kilogram of carbon converted to landfill gas, 71.2% is released as carbon dioxide and 28.8% is released as methane.

Energy recovery

This scenario includes shredding and combustion (module C3) with recovered energy offset against average electricity from the Australian grid and thermal energy from natural gas (module D) in line with EN 16485:2014 (Section 6.3.4.5).

Reuse (for plywood formwork only)

The product is assumed to be removed from a building manually and reused with no further processing (i.e. direct reuse). Transport and wastage are excluded and only one reuse cycle is considered. The second life is assumed to be the same (or very similar) to the first, meaning that a credit is given for production of 1 m² of primary plywood formwork in module D. The sequestered CO₂ and energy content of the wood are assumed to leave the system boundary at module C3 so that future product systems can also claim these without double-counting in line with EN 16485:2014 (Section 6.3.4.2). Any further processing, waste or transport would need to be modelled and included separately.

Recycling

Plywood may be recycled in many different ways. This scenario considers shredding and effectively downcycling into wood chips. Wood waste is chipped (module C3) and assigned credits relative to the avoided production of woodchips from virgin softwood, the primary material used for the veneers (module D). In line with the reuse scenario, the sequestered CO₂ and energy content of the wood are assumed to leave the system boundary at C3 so that future product systems can also claim these without double-counting (EN 16485:2014, Section 6.3.4.2).

Key Assumptions

Energy: All electricity and thermal energy inputs have been modelled as the Australian average (see thinkstep 2014 for documentation) rather than state-specific energy mixes. This is because the life cycle inventory data from the CSIRO study were aggregated and could not be split by state.

Cut-off Criteria

Environmental impacts relating to personnel, infrastructure, and production equipment not directly consumed in the process are excluded from the system boundary as per the PCR (IEPDS 2015, Section 6.5.4). Emissions from paint in the packaging stage are excluded in line with the original CSIRO (2009) study as they are assumed to be negligible. All other reported data were incorporated and modelled using the best available life cycle inventory data.

Allocation

Upstream data: For refinery products, allocation is done by mass and net calorific value. Inventories for electricity and thermal energy generation include allocation by economic value for some by-products (e.g. gypsum, boiler ash and fly ash). Allocation by energy is applied for co-generation of heat and power. For materials and chemicals, the allocation rule most suitable for the product is applied (see thinkstep 2014).

Co-products (e.g. veneer, clippings and sawdust): As the difference in economic value of the co-products is high (>25% as per EN 15804, Section 6.4.3.2), allocation has been done by economic value. Economic data were derived from ABARES (2014, Table 27).

Background Data

Data for wood inputs (softwood and hardwood veneer logs) come from CSIRO (2009) and use the same forestry data as EPD #01 for Softwood Timber and EPD #02 for Hardwood Timber, but with different economic allocation factors.

Data for all energy inputs, transport processes and raw materials are from GaBi Databases 2014 (thinkstep 2014). Most datasets have a reference year between 2011 and 2013 and all fall within the 10-year limit allowable for generic data under EN 15804 (Section 6.3.7).

All Australian electricity is assumed to be the 2011 national average with a Global Warming Potential of 1,004 g CO₂e/kWh, made up of 90% fossil fuel energy (46.6% hard coal, 21.9% lignite, 19.7% natural gas, 1.6% heavy fuel oil, 0.2% coal gases) and 10% renewable energy (6.7% hydro, 2.3% wind, 0.4% biomass, 0.4% biogas, 0.3% photovoltaic) (thinkstep 2014).

EPD Results

Note: these tables show the impacts associated with production and end-of-life. Any potential credits to future products from recycling or energy recovery are presented in the Other Environmental Information section.

Environmental Impact Indicators

An introduction to each environmental impact indicator is provided below. The best-known effect of each indicator is listed to the right of its name.


Global Warming Potential (GWP) → Climate Change

A measure of greenhouse gas emissions, such as carbon dioxide and methane. These emissions increase absorption of radiation emitted by the earth, intensifying the natural greenhouse effect. Contributions to GWP can come from either fossil or biogenic sources, e.g. burning fossil fuels or burning wood. GWP is reported both including biogenic carbon (GWPIB) and excluding biogenic carbon (GWPEB).




Ozone Depletion Potential (ODP) → Ozone Hole

A measure of air emissions that contribute to the depletion of the stratospheric ozone layer, causing higher levels of ultraviolet B (UVB) to reach the earth's surface with detrimental effects on humans, animals and plants.



Acidification Potential (AP) → Acid Rain

A measure of emissions that cause acidifying effects to the environment. Acidification potential is a measure of a molecule's capacity to increase the hydrogen ion (H^+) concentration in the presence of water, thus decreasing the pH value. Potential effects include fish mortality, forest decline and the deterioration of building materials.



Eutrophication Potential (EP) → Algal Blooms

A measure of nutrient enrichment that may cause an undesirable shift in species composition and elevated biomass production in both aquatic and terrestrial ecosystems. It includes potential impacts of excessively high levels of macronutrients, the most important of which are nitrogen (N) and phosphorus (P).



Photochemical Ozone Creation Potential (POCP) → Smog

A measure of emissions of precursors that contribute to ground level smog formation (mainly ozone O_3), produced by the reaction of VOCs and carbon monoxide in the presence of nitrogen oxides under the influence of UV light. Ground level ozone may be harmful to human and ecosystem health and may also damage crops.



Abiotic Depletion Potential → Resource Consumption

The consumption of non-renewable resources leads to a decrease in the future availability of the functions supplied by these resources. Depletion of mineral resource elements (ADPE) and non-renewable fossil energy resources (ADPF) are reported separately.



Table 3: Environmental impacts, 1 m² of interior plywood, C-bond, 9 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
GWPIB [kg CO ₂ -eq.]	-3.53E+00	9.12E-01	6.87E+00	8.57E+00	7.97E+00
GWPEB [kg CO ₂ -eq.]	4.38E+00	8.02E-01	5.06E+00	6.61E-01	5.50E-02
ODP [kg CFC11-eq.]	6.22E-11	4.74E-12	4.74E-12	3.96E-11	1.75E-12
AP [kg SO ₂ -eq.]	3.11E-02	1.69E-03	2.07E-03	3.68E-03	3.50E-04
EP [kg PO ₄ ³⁻ -eq.]	6.95E-03	6.43E-04	7.30E-03	8.79E-04	8.28E-05
POCP [kg C ₂ H ₄ -eq.]	6.96E-03	2.23E-04	1.38E-03	2.63E-04	3.70E-05
ADPE [kg Sb-eq.]	1.97E-06	1.01E-07	1.01E-07	8.62E-08	9.21E-10
ADPF [MJ]	5.88E+01	7.60E+00	7.60E+00	8.24E+00	7.09E-01

Table 4: Environmental impacts, 1 m² of exterior plywood, A-bond, 7 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
GWPIB [kg CO ₂ -eq.]	-2.26E+00	7.26E-01	5.63E+00	7.04E+00	6.20E+00
GWPEB [kg CO ₂ -eq.]	3.89E+00	6.39E-01	4.19E+00	8.86E-01	4.28E-02
ODP [kg CFC11-eq.]	5.69E-11	3.69E-12	3.69E-12	3.08E-11	1.36E-12
AP [kg SO ₂ -eq.]	2.41E-02	1.31E-03	1.63E-03	2.87E-03	2.72E-04
EP [kg PO ₄ ³⁻ -eq.]	4.92E-03	1.70E-04	2.56E-04	6.84E-04	6.44E-05
POCP [kg C ₂ H ₄ -eq.]	5.02E-03	1.77E-04	1.13E-03	2.05E-04	2.88E-05
ADPE [kg Sb-eq.]	2.15E-06	7.88E-08	7.88E-08	6.70E-08	7.16E-10
ADPF [MJ]	7.22E+01	5.91E+00	5.91E+00	1.04E+01	5.52E-01

Table 5: Environmental impacts, 1 m² of exterior plywood, A-bond, 9 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
GWPIB [kg CO ₂ -eq.]	-2.91E+00	9.34E-01	7.24E+00	9.05E+00	7.97E+00
GWPEB [kg CO ₂ -eq.]	5.00E+00	8.22E-01	5.39E+00	1.14E+00	5.50E-02
ODP [kg CFC11-eq.]	7.31E-11	4.74E-12	4.74E-12	3.96E-11	1.75E-12
AP [kg SO ₂ -eq.]	3.10E-02	1.69E-03	2.10E-03	3.68E-03	3.50E-04
EP [kg PO ₄ ³⁻ -eq.]	6.32E-03	2.18E-04	3.29E-04	8.79E-04	8.28E-05
POCP [kg C ₂ H ₄ -eq.]	6.46E-03	2.27E-04	1.45E-03	2.63E-04	3.70E-05
ADPE [kg Sb-eq.]	2.77E-06	1.01E-07	1.01E-07	8.62E-08	9.21E-10
ADPF [MJ]	9.29E+01	7.60E+00	7.60E+00	1.34E+01	7.09E-01

Table 6: Environmental impacts, 1 m² of formply, A-bond, 17 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Reuse	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3	C3
GWPIB [kg CO ₂ -eq.]	-5.50E+00	1.76E+00	1.37E+01	1.71E+01	1.49E+01	1.51E+01
GWPEB [kg CO ₂ -eq.]	9.44E+00	1.55E+00	1.02E+01	2.15E+00	0.00E+00	1.04E-01
ODP [kg CFC11-eq.]	1.38E-10	8.96E-12	8.96E-12	7.48E-11	0.00E+00	3.30E-12
AP [kg SO ₂ -eq.]	5.86E-02	3.19E-03	3.96E-03	6.96E-03	0.00E+00	6.62E-04
EP [kg PO ₄ ³⁻ -eq.]	1.19E-02	4.12E-04	6.22E-04	1.66E-03	0.00E+00	1.56E-04
POCP [kg C ₂ H ₄ -eq.]	1.22E-02	4.29E-04	2.75E-03	4.97E-04	0.00E+00	6.99E-05
ADPE [kg Sb-eq.]	5.23E-06	1.91E-07	1.91E-07	1.63E-07	0.00E+00	1.74E-09
ADPF [MJ]	1.75E+02	1.44E+01	1.44E+01	2.53E+01	0.00E+00	1.34E+00

Table 7: Environmental impacts, 1 m² of plywood flooring, A-bond, 15 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
GWPIB [kg CO ₂ -eq.]	-4.85E+00	1.56E+00	1.21E+01	1.53E+01	1.32E+01
GWPEB [kg CO ₂ -eq.]	8.33E+00	1.37E+00	9.05E+00	2.11E+00	9.17E-02
ODP [kg CFC11-eq.]	1.22E-10	7.90E-12	7.90E-12	6.60E-11	2.91E-12
AP [kg SO ₂ -eq.]	5.17E-02	2.81E-03	3.50E-03	6.14E-03	5.84E-04
EP [kg PO ₄ ³⁻ -eq.]	1.05E-02	3.64E-04	5.50E-04	1.47E-03	1.38E-04
POCP [kg C ₂ H ₄ -eq.]	1.08E-02	3.80E-04	2.44E-03	4.38E-04	6.17E-05
ADPE [kg Sb-eq.]	4.62E-06	1.69E-07	1.69E-07	1.44E-07	1.53E-09
ADPF [MJ]	1.55E+02	1.27E+01	1.27E+01	2.23E+01	1.18E+00

Table 8: Environmental impacts, 1 m² of plywood flooring, A-bond, 25 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
GWPIB [kg CO ₂ -eq.]	-8.08E+00	2.60E+00	2.02E+01	2.53E+01	2.20E+01
GWPEB [kg CO ₂ -eq.]	1.39E+01	2.29E+00	1.50E+01	3.38E+00	1.53E-01
ODP [kg CFC11-eq.]	2.03E-10	1.32E-11	1.32E-11	1.10E-10	4.85E-12
AP [kg SO ₂ -eq.]	8.62E-02	4.69E-03	5.83E-03	1.02E-02	9.73E-04
EP [kg PO ₄ ³⁻ -eq.]	1.76E-02	6.06E-04	9.16E-04	2.44E-03	2.30E-04
POCP [kg C ₂ H ₄ -eq.]	1.79E-02	6.32E-04	4.05E-03	7.31E-04	1.03E-04
ADPE [kg Sb-eq.]	7.69E-06	2.81E-07	2.81E-07	2.39E-07	2.56E-09
ADPF [MJ]	2.58E+02	2.11E+01	2.11E+01	3.72E+01	1.97E+00

Table 9: Resource use, 1 m² of interior plywood, C-bond, 9 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
PERE [MJ]	7.09E+01	3.80E-01	3.80E-01	7.31E+01	1.73E-02
PERM [MJ]	7.29E+01	0.00E+00	0.00E+00	-7.29E+01	-7.29E+01
PERT [MJ]	1.44E+02	3.80E-01	3.80E-01	2.45E-01	-7.29E+01
PENRE [MJ]	5.98E+01	7.77E+00	7.77E+00	8.61E+00	7.10E-01
PENRM [MJ]	5.09E+00	0.00E+00	0.00E+00	-5.09E+00	-5.09E+00
PENRT [MJ]	6.49E+01	7.77E+00	7.77E+00	3.52E+00	-4.38E+00
SM [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	3.54E-02	9.44E-05	7.58E-04	2.21E-02	1.47E-05
FWG [m ³]	4.20E+00	2.19E-03	2.19E-03	5.11E-04	2.82E-04
FWT [m ³]	4.23E+00	2.28E-03	2.94E-03	2.26E-02	2.96E-04

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials;

PERM = Use of renewable primary energy resources used as raw materials; *PERT* = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;

PENRM = Use of non-renewable primary energy resources used as raw materials; *PENRT* = Total use of non-renewable primary energy resources;

SM = Use of secondary material; *RSF* = Use of renewable secondary fuels; *NRSF* = Use of non-renewable secondary fuels;

FWB = Use of net blue water, i.e. water from rivers, lakes and aquifers; *FWG* = Use of net green water, i.e. rain water;

FWT = Total use of net fresh water

Table 10: Resource use, 1 m² of exterior plywood, A-bond, 7 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
PERE [MJ]	5.53E+01	2.96E-01	2.96E-01	5.69E+01	1.35E-02
PERM [MJ]	5.67E+01	0.00E+00	0.00E+00	-5.67E+01	-5.67E+01
PERT [MJ]	1.12E+02	2.96E-01	2.96E-01	1.91E-01	-5.67E+01
PENRE [MJ]	7.32E+01	6.04E+00	6.04E+00	1.07E+01	5.52E-01
PENRM [MJ]	7.96E+00	0.00E+00	0.00E+00	-7.96E+00	-7.96E+00
PENRT [MJ]	8.11E+01	6.04E+00	6.04E+00	2.74E+00	-7.41E+00
SM [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	3.29E-02	7.54E-05	6.21E-04	1.72E-02	1.15E-05
FWG [m ³]	3.26E+00	1.70E-03	1.70E-03	3.97E-04	2.19E-04
FWT [m ³]	3.30E+00	1.78E-03	2.32E-03	1.76E-02	2.30E-04

Table 11: Resource use, 1 m² of exterior plywood, A-bond, 9 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
PERE [MJ]	7.11E+01	3.80E-01	3.80E-01	7.31E+01	1.73E-02
PERM [MJ]	7.29E+01	0.00E+00	0.00E+00	-7.29E+01	-7.29E+01
PERT [MJ]	1.44E+02	3.80E-01	3.80E-01	2.45E-01	-7.29E+01
PENRE [MJ]	9.41E+01	7.77E+00	7.77E+00	1.38E+01	7.10E-01
PENRM [MJ]	1.02E+01	0.00E+00	0.00E+00	-1.02E+01	-1.02E+01
PENRT [MJ]	1.04E+02	7.77E+00	7.77E+00	3.52E+00	-9.53E+00
SM [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	4.23E-02	9.69E-05	7.99E-04	2.21E-02	1.47E-05
FWG [m ³]	4.20E+00	2.19E-03	2.19E-03	5.11E-04	2.82E-04
FWT [m ³]	4.24E+00	2.28E-03	2.98E-03	2.26E-02	2.96E-04

Table 12: Resource use, 1 m² of formply, A-bond, 17 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Reuse	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3	C3
PERE [MJ]	1.34E+02	7.18E-01	7.18E-01	1.38E+02	0.00E+00	3.30E-02
PERM [MJ]	1.38E+02	0.00E+00	0.00E+00	-1.38E+02	-1.38E+02	-1.38E+02
PERT [MJ]	2.72E+02	7.18E-01	7.18E-01	4.63E-01	-1.38E+02	-1.38E+02
PENRE [MJ]	1.78E+02	1.47E+01	1.47E+01	2.60E+01	0.00E+00	1.34E+00
PENRM [MJ]	1.93E+01	0.00E+00	0.00E+00	-1.93E+01	-1.93E+01	-1.93E+01
PENRT [MJ]	1.97E+02	1.47E+01	1.47E+01	6.65E+00	-1.93E+01	-1.80E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	8.00E-02	1.83E-04	1.51E-03	4.17E-02	0.00E+00	2.78E-05
FWG [m ³]	7.93E+00	4.13E-03	4.13E-03	9.65E-04	0.00E+00	5.32E-04
FWT [m ³]	8.01E+00	4.31E-03	5.64E-03	4.27E-02	0.00E+00	5.60E-04

Table 13: Resource use, 1 m² of plywood flooring, A-bond, 15 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
PERE [MJ]	1.19E+02	6.33E-01	6.33E-01	1.22E+02	2.90E-02
PERM [MJ]	1.21E+02	0.00E+00	0.00E+00	-1.21E+02	-1.21E+02
PERT [MJ]	2.40E+02	6.33E-01	6.33E-01	4.09E-01	-1.21E+02
PENRE [MJ]	1.57E+02	1.29E+01	1.29E+01	2.29E+01	1.18E+00
PENRM [MJ]	1.71E+01	0.00E+00	0.00E+00	-1.71E+01	-1.71E+01
PENRT [MJ]	1.74E+02	1.29E+01	1.29E+01	5.87E+00	-1.59E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	7.06E-02	1.62E-04	1.34E-03	3.68E-02	2.46E-05
FWG [m ³]	6.99E+00	3.64E-03	3.64E-03	8.51E-04	4.69E-04
FWT [m ³]	7.06E+00	3.80E-03	4.98E-03	3.77E-02	4.94E-04

Table 14: Resource use, 1 m² of plywood flooring, A-bond, 25 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
PERE [MJ]	1.98E+02	1.06E+00	1.06E+00	2.03E+02	4.90E-02
PERM [MJ]	2.02E+02	0.00E+00	0.00E+00	-2.02E+02	-2.02E+02
PERT [MJ]	4.00E+02	1.06E+00	1.06E+00	6.81E-01	-2.02E+02
PENRE [MJ]	2.61E+02	2.16E+01	2.16E+01	3.82E+01	1.97E+00
PENRM [MJ]	2.84E+01	0.00E+00	0.00E+00	-2.84E+01	-2.84E+01
PENRT [MJ]	2.90E+02	2.16E+01	2.16E+01	9.78E+00	-2.65E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	1.18E-01	2.70E-04	2.23E-03	6.14E-02	4.09E-05
FWG [m ³]	1.17E+01	6.07E-03	6.07E-03	1.42E-03	7.82E-04
FWT [m ³]	1.18E+01	6.34E-03	8.30E-03	6.28E-02	8.23E-04

Waste and Output Flows

Table 15: Waste categories, 1 m² of interior plywood, C-bond, 9 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
HWD [kg]	1.41E-04	1.28E-06	1.28E-06	8.35E-07	1.22E-07
NHWD [kg]	5.04E-01	5.30E+00	3.52E+00	2.05E-02	4.18E-05
RWD [kg]	3.84E-04	6.57E-05	6.57E-05	1.47E-04	1.10E-07
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.39E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	1.03E-01	1.70E+00	9.50E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	2.21E+01	0.00E+00

HWD = Hazardous waste disposed; *NHWD* = Non-hazardous waste disposed; *RWD* = Radioactive waste disposed;
CRU = Components for reuse; *MFR* = Materials for recycling; *MER* = Materials for energy recovery;
EEE = Exported electrical energy; *EET* = Exported thermal energy

Table 16: Waste categories, 1 m² of exterior plywood, A-bond, 7 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
HWD [kg]	1.11E-04	9.97E-07	9.97E-07	6.50E-07	9.51E-08
NHWD [kg]	3.95E-01	4.12E+00	2.68E+00	1.59E-02	3.25E-05
RWD [kg]	3.67E-04	5.11E-05	5.11E-05	1.15E-04	8.59E-08
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	4.19E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	8.49E-02	1.39E+00	7.39E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	1.72E+01	0.00E+00

Table 17: Waste categories, 1 m² of exterior plywood, A-bond, 9 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
HWD [kg]	1.43E-04	1.28E-06	1.28E-06	8.35E-07	1.22E-07
NHWD [kg]	5.08E-01	5.29E+00	3.45E+00	2.05E-02	4.18E-05
RWD [kg]	4.72E-04	6.57E-05	6.57E-05	1.47E-04	1.10E-07
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	5.39E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	1.09E-01	1.79E+00	9.50E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	2.21E+01	0.00E+00

Table 18: Waste categories, 1 m² of formply, A-bond, 17 mm.

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Reuse	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3	C3
HWD [kg]	2.70E-04	2.42E-06	2.42E-06	1.58E-06	0.00E+00	2.31E-07
NHWD [kg]	9.59E-01	1.00E+01	6.51E+00	3.86E-02	0.00E+00	7.89E-05
RWD [kg]	8.91E-04	1.24E-04	1.24E-04	2.79E-04	0.00E+00	2.09E-07
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.02E+01	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.02E+01
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	2.06E-01	3.39E+00	1.79E+01	0.00E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	4.18E+01	0.00E+00	0.00E+00

Table 19: Waste categories, 1 m² of plywood flooring, A-bond, 15 mm

	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
HWD [kg]	2.38E-04	2.14E-06	2.14E-06	1.39E-06	2.04E-07
NHWD [kg]	8.46E-01	8.82E+00	5.72E+00	3.41E-02	6.96E-05
RWD [kg]	7.86E-04	1.10E-04	1.10E-04	2.46E-04	1.84E-07
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	8.98E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	1.83E-01	3.01E+00	1.58E+01	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	3.69E+01	0.00E+00

Table 20: Waste categories, 1 m² of plywood flooring, A-bond, 25 mm


	Production	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Parameter [Unit]	A1-A3	C4	C4	C3	C3
HWD [kg]	3.97E-04	3.56E-06	3.56E-06	2.32E-06	3.40E-07
NHWD [kg]	1.41E+00	1.47E+01	9.55E+00	5.68E-02	1.16E-04
RWD [kg]	1.31E-03	1.83E-04	1.83E-04	4.10E-04	3.07E-07
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.50E+01
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	3.04E-01	5.00E+00	2.64E+01	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	6.14E+01	0.00E+00

Interpretation

Understanding the Life Cycle of Plywood

Life cycle of plywood

Life cycle carbon footprint in kg CO₂-equivalent per m² of 17 mm thick plywood formwork (A-bond; 12% moisture content), including biogenic and fossil carbon



Variation in Results

The data in this EPD are an average from multiple producers; however, there can be considerable variation between producers. Please contact your timber supplier if you require data on a specific product from that supplier.

Carbon Dioxide Sequestration

During growth, trees absorb carbon dioxide (CO₂) from the atmosphere through the process of photosynthesis and convert this into carbon-based compounds that constitute various components of a tree, including wood. On average, half the dry weight of all wood is made up of the element carbon. An Australian study (Gifford 2000) confirmed that 50±2% of the dry weight of the wood of native species and non-native *Pinus radiata* is carbon.

The CO₂ sequestered per cubic metre of wood was calculated using the formula specified in European standard EN 16449:2014:

$$P_{CO_2} = \frac{44}{12} \times cf \times \frac{\rho_w \times V_w}{1 + \frac{\omega}{100}}$$

Where:

- P_{CO_2} is the biogenic carbon sequestered in the wood that can be oxidised to a carbon dioxide emission to air
- $\frac{44}{12}$ is the molecular weight of carbon dioxide divided by the atomic weight of carbon
- cf is the carbon fraction of oven dry mass of woody biomass (0.5 is the default value)
- ω is the moisture content of the product on a dry basis (see Table 1)
- ρ_ω is the density of woody biomass at that moisture content (kg/m^3) (550 kg/m^3 for average Australian softwood at 12% moisture content)
- V_ω is the volume of the solid wood product at that moisture content (m^3) (note that only the wood fraction from Table 2 should be included).

All major Australian production forests and plantations are independently certified to one or both of the internationally recognised forest management certification systems: the Australian Standard for Sustainable Forest Management (AS 4708), which is recognised under the Programme for the Endorsement of Forest Certification (PEFC), and/or one of the Forest Stewardship Council's (FSC®) interim forest management standards. It is therefore appropriate to include biogenic CO₂ sequestration in this EPD in line with EN 16485 (Section 6.3.4.2). For more information on certification by forest owner or manager please see www.forestrystandard.org.au/find-certified/certified-forest-managers and info.fsc.org/certificate.php.

Water Consumption

Freshwater consumption is included in this EPD as required by PCR 2012:01. It has been split into blue water (i.e. water from lakes, rivers and aquifers) and green water (i.e. rain water). Blue water is usually metered and consumption is therefore based on physical measurements.

Green water consumption is difficult to quantify. The data included in this EPD are based on calculated differences in water flow between plantation and a base case land use (pasture) for softwood and differences between native forest and a base case land use (conservation) for hardwood from the original CSIRO LCI study (CSIRO 2009). The reader should be aware that these figures are uncertain and also provide no information about the impacts of water consumption, such as relative water stress in a given catchment where forest is harvested.

Changes to *Life Cycle Inventory of Australian Forestry and Wood Products*

The data in this EPD have been based on the *Life Cycle Inventory of Australian Forestry and Wood Products* (CSIRO 2009) with the underlying LCA models completely rebuilt in the GaBi LCA software and aligned with the modular structure of EN 15804. Through this process, assumptions in the CSIRO study have been re-examined, discrepancies corrected, consistency improved and data gaps filled. As such, the results in this EPD do not completely match those in the original CSIRO study. Furthermore, all end-of-life scenarios are new and were developed specifically for the Australian wood product EPDs produced in this series.

Other Environmental Information

Module D: Recycling, Reuse and Recovery Potentials

Table 21: Module D, 1 m² of interior plywood, C-bond, 9 mm.

Parameter [Unit]	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Environmental Impact				
GWPIB [kg CO ₂ -eq.]	-2.88E-02	-4.73E-01	-4.10E+00	-1.01E+00
GWPEB [kg CO ₂ -eq.]	-2.88E-02	-4.74E-01	-4.11E+00	-1.02E+00
ODP [kg CFC11-eq.]	-2.23E-14	-3.66E-13	-2.12E-12	-9.82E-12
AP [kg SO ₂ -eq.]	-1.26E-04	-2.07E-03	-1.38E-02	-8.79E-03
EP [kg PO ₄ ³⁻ -eq.]	-1.06E-05	-1.74E-04	-1.50E-03	-1.73E-03
POCP [kg C ₂ H ₄ -eq.]	-6.83E-06	-1.12E-04	-8.26E-04	-1.11E-03
ADPE [kg Sb-eq.]	-7.59E-10	-1.25E-08	-1.58E-07	-6.25E-08
ADPF [MJ]	-3.25E-01	-5.34E+00	-5.44E+01	-1.35E+01
Resource Use				
PERE [MJ]	-2.13E-02	-3.50E-01	-1.97E+00	-2.66E+01
PERM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT [MJ]	-2.13E-02	-3.50E-01	-1.97E+00	-2.66E+01
PENRE [MJ]	-3.25E-01	-5.34E+00	-5.44E+01	-1.36E+01
PENRM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT [MJ]	-3.25E-01	-5.34E+00	-5.44E+01	-1.36E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	5.39E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	-1.60E-04	-2.64E-03	-1.48E-02	-7.22E-03
FWG [m ³]	-1.71E-05	-2.81E-04	-1.64E-03	-3.27E-01
FWT [m ³]	-1.78E-04	-2.92E-03	-1.64E-02	-3.34E-01
Wastes and Outputs				
HWD [kg]	-5.71E-08	-9.39E-07	-7.60E-06	-4.93E-05
NHWD [kg]	-7.62E-05	-1.25E-03	-1.12E-02	-5.66E-02
RWD [kg]	-9.57E-08	-1.57E-06	-9.84E-06	-3.12E-05
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Table 22: Module D, 1 m² of exterior plywood, A-bond, 7 mm.

Parameter [Unit]	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Environmental Impact				
GWPIB [kg CO ₂ -eq.]	-2.37E-02	-3.89E-01	-3.19E+00	-7.87E-01
GWPEB [kg CO ₂ -eq.]	-2.37E-02	-3.89E-01	-3.19E+00	-7.92E-01
ODP [kg CFC11-eq.]	-1.83E-14	-3.01E-13	-1.65E-12	-7.63E-12
AP [kg SO ₂ -eq.]	-1.04E-04	-1.70E-03	-1.07E-02	-6.84E-03
EP [kg PO ₄ ³⁻ -eq.]	-8.70E-06	-1.43E-04	-1.17E-03	-1.35E-03
POCP [kg C ₂ H ₄ -eq.]	-5.62E-06	-9.23E-05	-6.42E-04	-8.61E-04
ADPE [kg Sb-eq.]	-6.24E-10	-1.03E-08	-1.23E-07	-4.86E-08
ADPF [MJ]	-2.67E-01	-4.39E+00	-4.23E+01	-1.05E+01
Resource Use				
PERE [MJ]	-1.75E-02	-2.88E-01	-1.53E+00	-2.07E+01
PERM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT [MJ]	-1.75E-02	-2.88E-01	-1.53E+00	-2.07E+01
PENRE [MJ]	-2.67E-01	-4.39E+00	-4.23E+01	-1.06E+01
PENRM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT [MJ]	-2.67E-01	-4.39E+00	-4.23E+01	-1.06E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	4.19E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	-1.32E-04	-2.17E-03	-1.15E-02	-5.62E-03
FWG [m ³]	-1.40E-05	-2.31E-04	-1.28E-03	-2.54E-01
FWT [m ³]	-1.46E-04	-2.40E-03	-1.28E-02	-2.60E-01
Wastes and Outputs				
HWD [kg]	-4.70E-08	-7.72E-07	-5.91E-06	-3.83E-05
NHWD [kg]	-6.26E-05	-1.03E-03	-8.71E-03	-4.40E-02
RWD [kg]	-7.87E-08	-1.29E-06	-7.66E-06	-2.43E-05
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Table 23: Module D, 1 m² of exterior plywood, A-bond, 9 mm.

Parameter [Unit]	Landfill (typical)	Landfill (NGA)	Energy recovery	Recycling
Environmental Impact				
GWPIB [kg CO ₂ -eq.]	-3.04E-02	-5.00E-01	-4.10E+00	-1.01E+00
GWPEB [kg CO ₂ -eq.]	-3.05E-02	-5.01E-01	-4.11E+00	-1.02E+00
ODP [kg CFC11-eq.]	-2.35E-14	-3.87E-13	-2.12E-12	-9.82E-12
AP [kg SO ₂ -eq.]	-1.33E-04	-2.19E-03	-1.38E-02	-8.79E-03
EP [kg PO ₄ ³⁻ -eq.]	-1.12E-05	-1.84E-04	-1.50E-03	-1.73E-03
POCP [kg C ₂ H ₄ -eq.]	-7.22E-06	-1.19E-04	-8.26E-04	-1.11E-03
ADPE [kg Sb-eq.]	-8.02E-10	-1.32E-08	-1.58E-07	-6.25E-08
ADPF [MJ]	-3.44E-01	-5.65E+00	-5.44E+01	-1.35E+01
Resource Use				
PERE [MJ]	-2.25E-02	-3.70E-01	-1.97E+00	-2.66E+01
PERM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT [MJ]	-2.25E-02	-3.70E-01	-1.97E+00	-2.66E+01
PENRE [MJ]	-3.44E-01	-5.65E+00	-5.44E+01	-1.36E+01
PENRM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT [MJ]	-3.44E-01	-5.65E+00	-5.44E+01	-1.36E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	5.39E+00
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	-1.70E-04	-2.79E-03	-1.48E-02	-7.22E-03
FWG [m ³]	-1.81E-05	-2.97E-04	-1.64E-03	-3.27E-01
FWT [m ³]	-1.88E-04	-3.08E-03	-1.64E-02	-3.34E-01
Wastes and Outputs				
HWD [kg]	-6.04E-08	-9.93E-07	-7.60E-06	-4.93E-05
NHWD [kg]	-8.05E-05	-1.32E-03	-1.12E-02	-5.66E-02
RWD [kg]	-1.01E-07	-1.66E-06	-9.84E-06	-3.12E-05
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Table 24: Module D, 1 m² of formply, A-bond, 17 mm.

Parameter [Unit]	Landfill (typical)	Landfill (NGA)	Energy recovery	Reuse	Recycling
Environmental Impact					
GWPIB [kg CO ₂ -eq.]	-5.75E-02	-9.45E-01	-7.75E+00	-9.44E+00	-1.91E+00
GWPEB [kg CO ₂ -eq.]	-5.76E-02	-9.46E-01	-7.76E+00	-9.44E+00	-1.92E+00
ODP [kg CFC11-eq.]	-4.45E-14	-7.30E-13	-4.01E-12	-1.38E-10	-1.85E-11
AP [kg SO ₂ -eq.]	-2.52E-04	-4.14E-03	-2.60E-02	-5.86E-02	-1.66E-02
EP [kg PO ₄ ³⁻ -eq.]	-2.11E-05	-3.47E-04	-2.83E-03	-1.19E-02	-3.28E-03
POCP [kg C ₂ H ₄ -eq.]	-1.36E-05	-2.24E-04	-1.56E-03	-1.22E-02	-2.09E-03
ADPE [kg Sb-eq.]	-1.52E-09	-2.49E-08	-2.99E-07	-5.23E-06	-1.18E-07
ADPF [MJ]	-6.49E-01	-1.07E+01	-1.03E+02	-1.75E+02	-2.56E+01
Resource Use					
PERE [MJ]	-4.26E-02	-7.00E-01	-3.72E+00	-1.34E+02	-5.03E+01
PERM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT [MJ]	-4.26E-02	-7.00E-01	-3.72E+00	-1.34E+02	-5.03E+01
PENRE [MJ]	-6.50E-01	-1.07E+01	-1.03E+02	-1.78E+02	-2.57E+01
PENRM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT [MJ]	-6.50E-01	-1.07E+01	-1.03E+02	-1.78E+02	-2.57E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	1.02E+01	1.02E+01
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	-3.21E-04	-5.27E-03	-2.79E-02	-8.00E-02	-1.36E-02
FWG [m ³]	-3.41E-05	-5.60E-04	-3.10E-03	-7.93E+00	-6.18E-01
FWT [m ³]	-3.55E-04	-5.83E-03	-3.10E-02	-8.01E+00	-6.31E-01
Wastes and Outputs					
HWD [kg]	-1.14E-07	-1.88E-06	-1.44E-05	-2.70E-04	-9.31E-05
NHWD [kg]	-1.52E-04	-2.50E-03	-2.11E-02	-9.59E-01	-1.07E-01
RWD [kg]	-1.91E-07	-3.14E-06	-1.86E-05	-8.91E-04	-5.89E-05
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Table 25: Module D, 1 m² of plywood flooring, A-bond, 15 mm.

Parameter [Unit]	Landfill (typical)	Landfill (NGA)	Energy recovery	Reuse	Recycling
Environmental Impact					
GWPIB [kg CO ₂ -eq.]	-5.10E-02	-8.39E-01	-6.84E+00	-1.69E+00	-1.91E+00
GWPEB [kg CO ₂ -eq.]	-5.11E-02	-8.39E-01	-6.84E+00	-1.70E+00	-1.92E+00
ODP [kg CFC11-eq.]	-3.95E-14	-6.48E-13	-3.54E-12	-1.64E-11	-1.85E-11
AP [kg SO ₂ -eq.]	-2.24E-04	-3.67E-03	-2.29E-02	-1.46E-02	-1.66E-02
EP [kg PO ₄ ³⁻ -eq.]	-1.88E-05	-3.08E-04	-2.50E-03	-2.89E-03	-3.28E-03
POCP [kg C ₂ H ₄ -eq.]	-1.21E-05	-1.99E-04	-1.38E-03	-1.84E-03	-2.09E-03
ADPE [kg Sb-eq.]	-1.35E-09	-2.21E-08	-2.64E-07	-1.04E-07	-1.18E-07
ADPF [MJ]	-5.76E-01	-9.46E+00	-9.06E+01	-2.26E+01	-2.56E+01
Resource Use					
PERE [MJ]	-3.78E-02	-6.21E-01	-3.28E+00	-4.44E+01	-5.03E+01
PERM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT [MJ]	-3.78E-02	-6.21E-01	-3.28E+00	-4.44E+01	-5.03E+01
PENRE [MJ]	-5.77E-01	-9.47E+00	-9.07E+01	-2.27E+01	-2.57E+01
PENRM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT [MJ]	-5.77E-01	-9.47E+00	-9.07E+01	-2.27E+01	-2.57E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	8.98E+00	1.02E+01
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	-2.84E-04	-4.67E-03	-2.46E-02	-1.20E-02	-1.36E-02
FWG [m ³]	-3.03E-05	-4.97E-04	-2.74E-03	-5.45E-01	-6.18E-01
FWT [m ³]	-3.15E-04	-5.17E-03	-2.74E-02	-5.57E-01	-6.31E-01
Wastes and Outputs					
HWD [kg]	-1.01E-07	-1.66E-06	-1.27E-05	-8.22E-05	-9.31E-05
NHWD [kg]	-1.35E-04	-2.22E-03	-1.87E-02	-9.44E-02	-1.07E-01
RWD [kg]	-1.70E-07	-2.79E-06	-1.64E-05	-5.20E-05	-5.89E-05
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Table 26: Module D, 1 m² of plywood flooring, A-bond, 25 mm.

Parameter [Unit]	Landfill (typical)	Landfill (NGA)	Energy recovery	Reuse	Recycling
Environmental Impact					
GWPIB [kg CO ₂ -eq.]	-8.49E-02	-1.39E+00	-1.14E+01	-2.81E+00	-1.91E+00
GWPEB [kg CO ₂ -eq.]	-8.50E-02	-1.40E+00	-1.14E+01	-2.83E+00	-1.92E+00
ODP [kg CFC11-eq.]	-6.56E-14	-1.08E-12	-5.90E-12	-2.73E-11	-1.85E-11
AP [kg SO ₂ -eq.]	-3.72E-04	-6.11E-03	-3.82E-02	-2.44E-02	-1.66E-02
EP [kg PO ₄ ³⁻ -eq.]	-3.12E-05	-5.12E-04	-4.17E-03	-4.82E-03	-3.28E-03
POCP [kg C ₂ H ₄ -eq.]	-2.01E-05	-3.31E-04	-2.29E-03	-3.07E-03	-2.09E-03
ADPE [kg Sb-eq.]	-2.24E-09	-3.67E-08	-4.40E-07	-1.74E-07	-1.18E-07
ADPF [MJ]	-9.58E-01	-1.57E+01	-1.51E+02	-3.76E+01	-2.56E+01
Resource Use					
PERE [MJ]	-6.28E-02	-1.03E+00	-5.46E+00	-7.40E+01	-5.03E+01
PERM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PERT [MJ]	-6.28E-02	-1.03E+00	-5.46E+00	-7.40E+01	-5.03E+01
PENRE [MJ]	-9.59E-01	-1.57E+01	-1.51E+02	-3.79E+01	-2.57E+01
PENRM [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PENRT [MJ]	-9.59E-01	-1.57E+01	-1.51E+02	-3.79E+01	-2.57E+01
SM [kg]	0.00E+00	0.00E+00	0.00E+00	1.50E+01	1.02E+01
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FWB [m ³]	-4.73E-04	-7.77E-03	-4.11E-02	-2.01E-02	-1.36E-02
FWG [m ³]	-5.03E-05	-8.27E-04	-4.56E-03	-9.08E-01	-6.18E-01
FWT [m ³]	-5.23E-04	-8.60E-03	-4.56E-02	-9.28E-01	-6.31E-01
Wastes and Outputs					
HWD [kg]	-1.68E-07	-2.77E-06	-2.11E-05	-1.37E-04	-9.31E-05
NHWD [kg]	-2.25E-04	-3.69E-03	-3.11E-02	-1.57E-01	-1.07E-01
RWD [kg]	-2.82E-07	-4.63E-06	-2.73E-05	-8.66E-05	-5.89E-05
CRU [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MFR [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
MER [kg]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EEE [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
EET [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

Timber & Forest Certification

Many Australian timber and reconstituted wood products are certified to a forest certification scheme. This certification is an independent auditing process that provides:

- Assurance that the timber is from well-managed forests certified to internationally and nationally accepted forest management standards
- Assurance that the timber is from legally harvested sources
- Chain of custody (CoC) certification extending from the forest to the end user, which is traceable throughout the supply chain.

Two schemes apply to Australian wood production forests. One is administered by the Australian Forestry Standard Ltd (AFS). The AFS scheme is also endorsed by the international Programme for Endorsement of Forest Certification (PEFC). The other scheme is administered by the Forest Stewardship Council (FSC®) Australia.

If a Green Star project elects to use the timber credit as part of their Green Star submission, the Green Building Council of Australia recognises PEFC-endorsed forest certification schemes (such as the Australian Forest Certification Scheme, AFCS) as well as FSC®. Compliance with the CoC certification rules of either forest certification scheme for at least 95% by value of timber products used in the project will meet the requirements for this credit point (GBCA 2014).

As of 2015, there are approximately 10.6 million hectares of native and plantation forests certified in Australia, consisting of 10.1 million hectares certified under AFS and 900,000 hectares certified under FSC® (Australian Government 2015); 400,000 hectares are certified under both schemes.

In addition many Australian softwood manufacturers' premises listed in this EPD are CoC certified so they can supply products with CoC certification.

Land Use and Biodiversity

Like other land uses, forestry operations for timber and wood production can have both positive and negative effects on biodiversity. However, as biodiversity varies considerably by region and as data are often limited, assessing potential biodiversity impacts within LCA is challenging.

A recent Australian study (Turner *et al.* 2014) demonstrated a new method – BioImpact – to discern the biodiversity impacts of different land uses. A trial of this method was conducted using case studies in three different regions and four production systems in New South Wales: native hardwood forestry, plantation softwood forestry, mixed cropping and rangeland grazing. The results showed that the biodiversity impacts of native hardwood production in the region studied were significantly lower than the land uses in the other regions. The management of planted softwood forests resulted in similar biodiversity impacts to those of the cropping/grazing systems.

Indoor Environment Quality – Formaldehyde Emissions Minimisation

Formaldehyde is a colourless, strong-smelling gas that occurs naturally in the environment. It is present in the air that we breathe at natural background levels of about 0.03 parts per million (ppm) and up to 0.08 ppm in outdoor urban air (EWPAA 2012). Formaldehyde is used as an ingredient in synthetic resins, industrial chemicals and preservatives, and in the production of paper, textiles, cosmetics, disinfectants, medicines, paints, varnishes and lubricants.

The majority (>90%) of plywood products are manufactured in Australia using the adhesive phenol formaldehyde (PF). A small volume (<10%) is produced using an amino plastic, which includes melamine urea formaldehyde (MUF) and urea formaldehyde (UF).

To assure end users that they are using plywood with the lowest possible formaldehyde emissions, an industry-wide formaldehyde testing and labelling program is run by the Engineered Wood Products Association of Australasia. All mills are required to forward samples to EWPAA's National Laboratory on a regular basis for formaldehyde emission testing. On the basis of these laboratory tests, certified mills are permitted to brand a formaldehyde emission class on their plywood products as detailed in Table 27.

Table 27: Formaldehyde emission classes.

Emission class	Emission limit (mg/litre)	Emission limit (ppm)*	Adhesive associated with emission class
Super E0 / (equivalent to F☆☆☆☆)	Less than or equal to 0.3	Less than or equal to 0.03	A-bond (phenol formaldehyde)
E0	Less than or equal to 0.5	Less than or equal to 0.04	B and C bonds (melamine urea formaldehyde and urea formaldehyde)
E1	Less than or equal to 1.0	Less than or equal to 0.08	B and C bonds (melamine urea formaldehyde and urea formaldehyde)

** Based on a test chamber volume of 10litre, zero airflow during the 24hr test cycle, molecular weight of formaldehyde 30.03 and the number of microlitres of formaldehyde gas in 1 micromole at 101KPa and 298K.*

All Australian manufacturers listed in this EPD can supply test certificates that support their emission class.

Plywood with formaldehyde emissions less than or equal to Super E0 (the majority of Australian produced plywood products) are compliant with the Green Star Formaldehyde credit. Other plywood products, which have emissions less than or equal to E1, are also compliant. To achieve credit point(s) all engineered wood products such as particleboard, MDF and plywood used in the project must be in accordance with these requirements.

References

- ABARES. (2013). *Australia's State of the Forests Report 2013*. Canberra: Australian Bureau of Agricultural and Resource Economics and Sciences.
- ABARES. (2014). *Australian forest and wood products statistics: March and June quarters 2014*. Australian Bureau of Agricultural and Resource Economics. Available at <http://www.agriculture.gov.au/abares/forestsaustralia/australian-forest-and-wood-products-statistics>
- AEPDP. (2015). *General Programme Instructions of the Australasian EPD® Programme, Version 1.0, 2015-02-20*. Available at http://epd-australasia.com/sites/default/files/documents/Australasian_GPI_1.0.pdf
- Australian Government. (2014a). *National Inventory Report 2012, Volume 3: Australia data for waste, recalculations, improvements and Kyoto Protocol accounting requirements*. Australian National Greenhouse Accounts. Available at <http://www.environment.gov.au/climate-change/greenhouse-gas-measurement/publications/national-inventory-report-2012>
- Australian Government. (2014b). *National Greenhouse Accounts Factors*. Department of Environment.
- Australian Government. (2014c). *Technical Guidelines for the Estimation of Greenhouse Gas Emissions by Facilities in Australia*. Department of Environment.
- Australian Government. (2015). *Forest Certification in Australia*. Department of Agriculture. Available at <http://www.agriculture.gov.au/forestry/australias-forests/certification>
- Barlaz, M. (1998). Carbon storage during biodegradation of municipal solid waste components in laboratory scale landfills. *Global Biogeochemical Cycles*, 12 (2), 373–380.
- Blue Environment. (2013). *Analysis of landfill survey data*. Final report prepared for Waste Management Association of Australia. Available at <http://www.environment.gov.au/protection/national-waste-policy/publications/analysis-landfill-survey-data>
- Carre, A. (2011). *A Comparative Life Cycle Assessment of Alternative Constructions of a Typical Australian House Design*. Melbourne: Forest & Wood Products Australia. Available at http://www.fwpa.com.au/images/marketaccess/PNA147-0809_Research_Report_Comparative-LCA_0.pdf
- CSIRO. (2009). (Prepared by Tucker, S.N.; Tharumarajah, A.; May, B.; England, J.; Paul, K.; Hall, M.; Mitchell, P.; Rouwette, R.; Seo, S. and Syme, M.) *Life Cycle Inventory of Australian Forestry and Wood Products*. Prepared by the Commonwealth Scientific and Industrial Research Organisation on behalf of Forest and Wood Products Australia. Project number PNA008-0708.
- EN 15804:2012+A1:2013. *Sustainability of construction works – Environmental product declarations - Core rules for the product category of construction products*. Brussels: European Committee for Standardization.
- EN 16449:2014. *Wood and wood-based products – Calculation of the biogenic carbon content of wood and conversion to carbon dioxide*. Brussels: European Committee for Standardization.
- EN 16485:2014. *Round and sawn timber - Environmental Product Declarations - Product category rules for wood and wood-based products for use in construction*. Brussels: European Committee for Standardization.

EWPA. (2012). *Facts About Formaldehyde Emissions from EWPA Certified Products*. Engineered Wood Products Association of Australasia. Available at http://www.ewp.asn.au/library/downloads/ewpaa_formaldehyde_facts.pdf

Forsythe Consultants. (2007). *Mapping the Timber Waste Stream from Building Demolition*. Available at http://www.timberstewardship.org.au/images/pdf_documents/demolition_waste_barriers_final.pdf

Gavran, M., Burns, K., Hug, B., Frakes, I. and Gupta, M. (2014). *ABARES National Wood Processing Survey 2012–13*. Research by the Australian Bureau of Agricultural and Resource Economics and Sciences. Research report 14.6.

GBCA. (2014). *Revised Timber Credit*. Green Building Council of Australia. Available at <https://www.gbca.org.au/green-star/technical-support/materials-category/revised-timber-credit/2693.htm>

Gifford, R. (2000). *Carbon Contents of Above-Ground Tissues of Forest and Woodland Trees*. Technical report No. 22. National Carbon Accounting Scheme. Australian Greenhouse Office. Available at <http://pandora.nla.gov.au/pan/23322/20020220-0000/www.greenhouse.gov.au/ncas/files/pdfs/tr22final.pdf>

Hyder Consulting Group. (2007). *Review of Methane Recovery and Flaring from Landfills*. Australian Greenhouse Office, Department of Environment and Water Resources.

IEPDS. (2015). *PCR 2012:01, Construction products and Construction services, Version 2.0, 2015-03-03*. Stockholm: International EPD® System. Available at: <http://www.environdec.com/en/PCR/Detail/?Pcr=8098>

ISO 14025:2006. *Environmental labels and declarations — Type III environmental declarations - Principles and procedures*. Geneva: International Organization for Standardization.

National Timber Product Stewardship Group. (2015). Available at www.timberstewardship.org.au

thinkstep. (2014). *GaBi life cycle inventory database documentation*. Leinfelden-Echterdingen, Germany: thinkstep AG. URL: <http://database-documentation.gabi-software.com/support/gabi/gabi-database-2014-lci-documentation/>

Turner, P., Ximenes, F., Penman, T., Law, B., Waters, C., Mo, M. and Brock, P. (2014). *Accounting for biodiversity in Life Cycle Impact Assessments of forestry and agricultural systems – the BioImpact metric*. Research report for Forest & Wood Products Australia Limited. Available at <http://www.fwpa.com.au>

Wang, W., Padgett, J., De La Cruz, F. and Barlaz, M. (2011). *Wood biodegradation in laboratory-scale landfills*. *Environmental Science & Technology*, 45(16), pp. 6864-6871.

WoodSolutions. (2012). *Timber Service Life Design Guide*. Available at <https://www.woodsolutions.com.au/Articles/Resources/Timber-Service-life-design>

WoodSolutions. (2015). *Timber Preservation*. Available at <http://www.woodsolutions.com.au/Articles/Resources/Timber-Preservation>

Ximenes, F., Brooks, P., Wilson, C. and Giles, D. (2013). *Carbon Storage in Engineered Wood Products in Landfills*. Forest and Wood Products Australia. Available at <http://www.fwpa.com.au/rd-and-e/processing/181-carbon-storage-in-engineered-wood-products-in-landfills.html>