



QUICK RENDER RANGE

Serving solid plasterers for 40 years.

Why use Rockcote's Quick Render range?



Range

- ✓ Unrivalled product quality and consistency means
 - No surprises on site
 - Ready to over coat in 48 hours
 - Full product warranties.
- ✓ The Quick Render range has a product for every substrate and every project.



Manufacturing

- ✓ State of the art control system to ensure consistent product quality.
- ✓ 100% water self sufficient plant means no town water and no additional cost to you.
- ✓ Capacity of 160,000kg per shift, means our products are always available when you need them.



Experience

- ✓ Designed by solid plasterers for solid plasterers.
- ✓ For over 40 years, Rockcote has been serving solid plasterers, so we know what you need from your renders.

Application

By Hand

Quick and easy to apply off the trowel, which keeps you moving quickly.



By Machine

All Quick Renders are suitable for machine application so you can ramp up your productivity.

The positive alternative to 'site mix' render

(sand & cement)

Quick Render Benefits

- ✓ 48 hours curing time
- ✓ Cost savings
- ✓ Quality and consistency
- ✓ No wastage
- ✓ Range of renders to suit various substrates, see Rockcote website for more details
- ✓ Water Resistant
- ✓ Healthy workplace
- ✓ Manufactured in Australia's premier state of the art render plant

Site mix

- ✗ 21—28 day curing time
- ✗ More scaffold hire time
- ✗ Higher risk of contamination
- ✗ Mess on site
- ✗ Soaks up water easily
- ✗ Greater risk of cracking, crazing and deterioration (due to inconsistent mixes)
- ✗ General purpose sand dumped on site from a landscape yard, then mixed on site with other unmeasured ingredients
- ✗ Greater risk of efflorescence



Rockcote Quick Render



Site Mix

Background on Efflorescence

- › Efflorescence is caused by the migration of salts in water through the wall.
- › Rockcote's render is formulated so salts are not present to cause efflorescence.
- › Rockcote's render is formulated so moisture migration is restricted (i.e. water resistant).
- › Both these actions prevent efflorescence occurring on Rockcote render.



Example of Efflorescence

Rockcote's Dry Mix Render Plant

- › Cutting edge of pre-mixed render technology
- › The first plant of its type in Australia
- › State-of-the-art control system, ensuring consistent product quality
- › Energy efficient
- › Greater raw material control, ensuring identical sand analysis each and every time
- › Capacity - 160 tonnes per shift - 8,000 bags



Rockcote Quick Render range

Product	Feature / Benefit	Colour	Sand Profile	Typical Coating Thickness	Set Time*	Cure Time	Compliance	Tools
 Super Fine	The finest of our Quick Render range and is designed for a smooth render finish	Off White	Super Fine	4mm Min 10mm Max	2-3 Hours*	48-72 Hours		Trowel or Pump
 Fine	Used where a finer and smoother textured render finish is required	Blend: Off White & Grey	Fine	4mm Min 10mm Max	2 Hours*	48-72 Hours		Trowel or Pump
 Off White	Dries harder, more quickly than Quick Render Grey	Off White	Medium Fine	4mm Min 10mm Max	2 Hours*	48-72 Hours		Trowel or Pump
 Premium Sponge	Can be applied as thin as 2mm without the additional need of bond	Off White	Medium Fine	2mm Min 10mm Max	2-2.5 Hours*	48-72 Hours		Trowel or Pump
 Grey	Ideal for use in harsher drying conditions where a slower drying rate is required	Grey	Medium	4mm Min 10mm Max	2-3 Hours*	48-72 Hours		Trowel or Pump
 Non-Combustible	Medium render finish either floated ready for texture or sponge finish	Grey	Medium	5mm Min 10mm Max	2-3 Hours*	48-72 Hours		Trowel or Pump
 High Strength	Optimised for high early strength at lower coating thicknesses	Off White	Medium	4mm Min 10mm Max	2 Hours*	48-72 Hours		Trowel or Pump
 PM100	A pre-blended polymer-modified cement render with excellent durability	Grey	Medium	4mm Min 10mm Max	2-2.5 Hours*	48-72 Hours		Trowel or Pump
 PM100 High Build	Can be built out to 30mm	Off White	N/A	5mm Min 30mm Max	3-12 Hours* depending on thickness	48-72 Hours		Trowel or Pump
 Quick Float	Perfect basecoat render with specific blend of sands enables a very user friendly product for floating	Off White	Medium Coarse	4mm Min 10mm Max	2 Hours*	48-72 Hours		Trowel or Pump
 Coarse	The Coarsest of our Quick render range, designed for a fast and easy float finish	Off White	Coarse	4mm Min 10mm Max	2 Hours*	48-72 Hours		Trowel or Pump

*Under normal drying conditions. Dry times vary with changes in temperature and humidity and residual moisture in the substrate.

